



Network

Multi-sensor

TNM-C4940TD

Bi-spectrum AI Thermal Camera



Key Features

- Bi-spectrum: VGA thermal & 8MP visible sensor
- Dual (thermal & visible) channel by one device, one IP
- Maximum 30fps @ all resolutions (H.265/H.264)
- Lens : 9.1mm fixed thermal & 4.4-9.3mm motorized varifocal visible
- Day & Night(ICR), WDR(120dB)
- Maximum IR viewable length : 30m
- Noise reduction : WiseNR II (Based on AI engine, visible only)
- Smart codec : WiseStream III (Based on AI engine, visible), WiseStream II (thermal)
- Video Analytics based on AI (visible)
- IP66/IP67, NEMA4X
- PoE+(IEEE802.3at), 12VDC
- Wall & Pole mount all-in-one design

TNM-C4940TD

Bi-spectrum AI Thermal Camera



Specifications

Video	Thermal	Visible
Imaging Device	Uncooled micro bolometer	1/1.8" CMOS
Resolution	640x480 (can be scaled up to 1280x960) 1280x960, 1280x720, 1024x768, 800x600, 800x448, 720x576, 720x480, 640x480, 640x360	3840x2160, 3072x1728, 2592x1944, 2688x1520, 2560x1440, 2048x1536, 1920x1080, 1600x1200, 1280x1024, 1280x960, 1280x720, 1024x768, 800x600, 800x448, 720x576, 720x480, 640x480, 640x360
Max. Framerate	H.265/H.264: Max. 30fps/25fps (AI 2CH ON - 15fps) MJPEG: Max. 3fps	H.265/H.264: Max. 30fps/25fps (AI 2CH ON - 15fps) MJPEG: Max. 1fps
NETD	<60mK	
Pixel Size	12μm	
Min. Illumination		Color: 0.06Lux(F1.3, 1/30sec) BW: 0.004Lux(F1.3, 1/30sec), 0Lux(IR LED on)
Video Out	USB : Micro USB Type B, 1280x720 for installation	
Lens		
Focal Length (Zoom Ratio)	9.1mm fixed focal	4.4~9.3mm(2.2x) motorized varifocal
Max. Aperture Ratio	F1.0	F1.3(Wide)~F2.15(Tele)
Angular Field of View	H: 50.0-, V: 37.0-, D: 63.8-	H:112.1°(Wide)~47.5°(Tele) / V:58.0°(Wide)~26.6°(Tele) / D:137.5°(Wide)~54.6°(Tele)
Min. Object Distance	3.5m(11.48ft)	Wide: 1.75m(5.74ft) / Tele: 5.21m(17.09ft)
Focus Control	Fixed	Simple focus
Operational		
Camera Title	Displayed up to 85 characters	
Day & Night	Auto(ICR)	
Backlight Compensation	BLC, WDR, SSDR	
Wide Dynamic Range	WDR(120dB)	
Digital Noise Reduction	SSNR V, WiseNR II	
Digital Image Stabilization	Support(built-in gyro sensor)	
Motion Detection	8ea, polygonal zones	
Privacy Masking	6ea, rectangle zones - Color: Gray/Black/White	
Gain Control	Low / Middle / High	
White Balance	ATW / AWC / Manual / Indoor / Outdoor	
LDC	Support	
Electronic Shutter Speed	Minimum / Maximum / Anti flicker(1/5~1/12,000sec) Auto prefer shutter control(Based on AI engine)	

Analytics	<ul style="list-style-type: none"> - Analytics events based on AI engine : Object detection (Person/Vehicle), Bestshot, IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Stopped vehicle, Traffic jam - Analytics events : Motion detection 	<p>Analytics events based on AI engine</p> <ul style="list-style-type: none"> - Object detection(Person, face, Vehicle(car/bus/truck/motorcycle/bicycle), License plate), Virtual line*(Crossing/Direction), Virtual area*(Loitering/Intrusion/Enter/Exit) <p>- Analytics events : Defocus detection, Motion detection, Tampering, Audio detection, Sound classification, Shock detection, Virtual area(Appear/Disappear)</p>
Business Intelligence	Vehicle counting	Vehicle counting
Alarm I/O	4 configurable I/O ports	
Alarm Triggers	Analytics, Network disconnect, Alarm input	
Alarm Events	<p>When alarm trigger occurred</p> <ul style="list-style-type: none"> - File upload(image) : e-mail/FTP - Notification : e-mail - Recording : SD/SDHC/SDXC or NAS recording at event triggers - Alarm output - Handover(PTZ preset, Send message by HTTP/HTTPS/TCP) - Audio clip playback 	
Audio In	<p>Selectable(mic in/line in)</p> <p>Supply voltage: 2.5VDC(4mA), Input impedance: 2K Ohm</p>	
Audio Out	Line out, Max.output level: 1Vrms	
IR Viewable Length	30m (98.42ft)	
Color Palettes	Whitehot, Blackhot, Rainbow, Rainbow2, Sepia, Red, Iron, Custom	
Network		
Ethernet	Metal shielded RJ-45(10/100/1000BASE-T)	
Video Compression	H.265/H.264: Main/High, MJPEG	
Audio Compression	<p>G.711 u-law / G.726 Selectable</p> <p>G.726(ADPCM) 8KHz, G.711 8KHz</p> <p>G.726: 16Kbps, 24Kbps, 32Kbps, 40Kbps</p> <p>AAC-LC: 48Kbps at 16KHz</p>	
Smart Codec	WiseStream II	Manual(5ea area), WiseStreamIII
Video Quality Adjustment	<p>H.264/H.265: Target bitrate level control</p> <p>MJPEG: Target bitrate level control</p>	
Bitrate Control	<p>H.264/H.265: CBR or VBR</p> <p>MJPEG: VBR</p>	
Streaming	<p>Unicast(6 users) / Multicast</p> <p>Multiple streaming(Up to 3 profiles)</p>	
Protocol	<p>IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP,RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP, SRTP (TCP, UDP Unicast)</p>	
Security	<p>TPM 2.0 (FIPS 140-2 level 2)</p> <p>HTTPS(SSL) login authentication</p> <p>Digest login authentication</p> <p>IP address filtering</p> <p>User access log</p> <p>802.1X authentication(EAP-TLS, EAP-LEAP, EAP-PEAP MSCHAPv2)</p> <p>Device certificate(Hanwha Techwin Root CA, pre-installed)</p> <p>Secure boot, Secure firmware</p>	
Application Programming Interface	<p>ONVIF Profile S/T</p> <p>SUNAPI(HTTP API)</p> <p>Wisenet open platform (visible channel only)</p>	
General		
Webpage Language	English, French, German, Spanish, Italian, Chinese, Korean, Russian, Japanese, Portuguese, Czech, Polish, Turkish, Dutch, Hungarian, Greek	
Edge Storage	Micro SD/SDHC/SDXC 2slots 512GB	
Memory	4GB RAM, 512MB FLASH	

Environmental & Electrical

Operating Temperature / Humidity	-40°C to +60°C(-58°F to +140°F) * Start up should be done at above -30°C less than 95% RH(non-condensing)
Storage Temperature / Humidity	-50°C to +60°C(-58°F to +140°F) / Less than 95% RH(Non-condensing)
Certification	IP66/IP67, IK10, NEMA4X, NEMA TS 2(2.2.8, 2.2.9)
Input Voltage	PoE+(IEEE802.3at, Class4), 12VDC
Power Consumption	PoE+ : Max 25.5W, Typ 16.0W 12VDC : Max 21.5W, Typ 14.0W

Mechanical

Color / Material	White / Aluminum
RAL Code	RAL9003
Product Dimensions / Weight	353.4 * 287.5 * 191.2mm (13.92 * 11.32 * 7.53in) / 4.533kg

DORI (EN62676-4 standard)

Detect (25PPM/ 8PPF)	Wide: 51.7m(169.94ft) / Tele: 174.5m(572.64ft)
Observe (63PPM/ 19PPF)	Wide: 20.7m(67.85ft) / Tele: 69.8m(229.06ft)
Recognize (125PPM/ 38PPF)	Wide: 10.3m(33.93ft) / Tele: 34.9m(114.53ft)
Identify (250PPM/ 76PPF)	Wide: 5.2m(16.96ft) / Tele: 17.5m(57.26ft)