

QND-8010R/8020R/8030R

5MP Network IR Dome Camera



QND-8010R





QND-8020R/8030R

Key Features

- Max. 5Megapixel (2592 x 1944) resolution
- 2.8mm/4mm/6mm fixed lens
- 0.15Lux (Color), 0Lux (B/W, IR LED on)
- Max. 30fps@5MP (H.265 / H.264)
- H.265, H.264, MJPEG codec support, Multiple streaming
- Day & Night, WDR (120dB)
- Tampering, Motion detection, Defocus detection
- Micro SD / SDHC / SDXC memory slot (Max. 128GB)
- Hallway view, WiseStream II support
- IR Viewable length 20m, PoE

Dimensions

Unit : mm (inch)



Accessories (Optional)



SBP-120WMW



SBP-300HMW7



SBP-300LMW



SBP-300CMW



SBP-300WMW1



SBP-300WMW

| | QND-8010R | QND-8020R | QND-8030R |
|-----------------------------------|--|--|--|
| VIDEO | | | |
| Imaging Device | 1/2.8" 5MP CMOS | | |
| Effective Pixels | 2592(H) x 1944(V) | | |
| Min. Illumination | Color : 0.15Lux (F2.0, 1/30sec) BW : 0Lux (IR LED on) | Color : 0.15Lux (F1.6, 1/30sec) BW : 0Lux (IR LED on) | Color : 0.15Lux (F2.0, 1/30sec) BW : 0Lux (IR LED on) |
| Video Out | CVBS : 1.0 Vp-p / 75Ω composite, 720 x 480(N), 720 x 576(P) for installation | | |
| LENS | | | |
| Focal Length (Zoom Ratio) | 2.8mm fixed focal | 4.0mm fixed focal | 6.0mm fixed focal |
| Max. Aperture Ratio | F2.0 | F1.6 | F2.0 |
| Angular Field of View | H : 104.7°/V : 76.5°/D : 136.0° | H : 79.8°/V : 58.1°/D : 105.9° | H : 49.4°/V : 37.4°/D : 61.0° |
| Focus Control | Fixed | | |
| PAN / TILT / ROTATE | | | |
| Pan / Tilt / Rotate Range | 0°~350° / 0°~67° / 0°~355° | | |
| OPERATIONAL | | | |
| IR Viewable Length | 20m (65.62ft) | | |
| Camera Title | Displayed up to 85 characters | | |
| Day & Night | Auto (ICR) | | |
| Backlight Compensation | BLC, WDR, SDR | | |
| Wide Dynamic Range | 120dB | | |
| Digital Noise Reduction | SSNR | | |
| Motion Detection | 4ea, polygonal zones | | |
| Privacy Masking | 6ea, rectangular zones | | |
| Gain Control | Low / Middle / High | | |
| White Balance | ATW / AWC / Manual / Indoor / Outdoor | | |
| LDC | Support | | |
| Electronic Shutter Speed | Minimum / Maximum / Anti flicker (1/5~1/12,000sec) | | |
| Video Rotation | Flip, Mirror, Hallway view (90°/270°) | | |
| Analytics | Defocus detection, Directional detection, Motion detection, Enter/Exit, Tampering, Virtual line | | |
| Alarm I/O | Input 1ea / Output 1ea | | |
| Alarm Triggers | Analytics, Network disconnect, Alarm input | | |
| Alarm events | File upload via FTP and e-mail, Notification via e-mail, SD/SDHC/SDXC or NAS recording at event triggers, Alarm output | | |
| NETWORK | | | |
| Ethernet | RJ-45 (10/100BASE-T) | | |
| Video Compression | H.265/H.264 : Main/High, MJPEG | | |
| Resolution | 2592 x 1944, 1920 x 1080, 1280 x 960, 1280 x 720, 800 x 600, 800 x 448, 720 x 576, 720 x 480, 640 x 480, 640 x 360 | | |
| Max. Framerate | H.265/H.264 : Max. 30fps/25fps (60Hz/50Hz) / MJPEG : Max. 15fps/12fps (60Hz/50Hz) | | |
| Smart Codec | WiseStream II | | |
| Video Quality Adjustment | H.264/H.265 : Target bitrate level control MJPEG : Quality level control | | |
| Bitrate Control | H.264/H.265 : CBR or VBR / MJPEG : VBR | | |
| Streaming | Unicast (6 users) / Multicast / Multiple streaming (Up to 3 profiles) | | |
| Protocol | IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP | | |
| Security | HTTPS (SSL) login authentication, Digest login authentication, IP address filtering, User access log, 802.1X authentication (EAP-TLS, EAP-LEAP) | | |
| Edge Storage | Micro SD/SDHC/SDXC 1slot 128GB | | |
| Application Programming Interface | ONVIF Profile S/G/T SUNAPI (HTTP API) Wisenet open platform | | |
| Webpage Language | English, Korean, Chinese, French, Italian, Spanish, German, Japanese, Russian, Swedish, Portuguese, Czech, Polish, Turkish, Dutch | | |

| | QND-8010R | QND-8020R | QND-8030R |
|----------------------------------|---|------------------------------|-----------|
| Web Viewer | Supported OS : Windows 7, 8.1, 10, Mac OS X 10.10, 10.11, 10.12, 10.13, 10.14 Recommended Browser : Google Chrome Supported Browser : MS Explorer11, MS Edge, Mozilla Firefox (Windows 64bit only), Apple Safari (Mac OS X only) | | |
| Memory | 512MB RAM, 256MB Flash | | |
| ENVIRONMENTAL | | | |
| Operating Temperature / Humidity | -10°C ~ +50°C (+14°F ~ +122°F) / Less than 90% RH | | |
| Storage Temperature / Humidity | -30°C ~ +60°C (-22°F ~ +140°F) / Less than 90% RH | | |
| ELECTRICAL | | | |
| Input Voltage | PoE (IEEE802.3af, Class3) | | |
| Power Consumption | PoE : Max 7.5W, typical 5.8W | PoE : Max 6.8W, typical 5.0W | |
| MECHANICAL | | | |
| Color / Material | White / Plastic | | |
| RAL Code | RAL9003 | | |
| Product dimensions / weight | Ø110.6 x 89.5mm (Ø4.35 x 3.52"), 360g (0.794 lb) | | |

* The latest product information / specification can be found at hanwha-security.com

* Design and specifications are subject to change without notice.

* Wisenet is the proprietary brand of **Hanwha Techwin**.